

SLV15CNK

تقنية :Category

2024 ، نوفمبر، written by Mahdi MILED | 23



Picture Private Copyright WWW.MBSMGROUP.TN

Compressor SLV15CNK.2 50/60Hz 220-240V refrigerant R290 height 199 mm LBP 12 kg displacement 15,28cm³

ATHEN210XL

Compressor SLV15CNK.2. Speed: 2000/2500/3000/4000 rev/min More features: LBP 12 kg displacement 15.2 cm frequency:50/60Hz 12kg 15,28 cm 3 Height: 199mm Refrigerant: R290 power at -15°C: 615/792/996/10 228 W power at -20°C: 467/602/759/941 W power at -25°C: 39°C: 39°C: 39°C: 3/509/645/805 W 311/402/510/638 W tension: 22 0-240 V

:Technical Details of AHT Athen XL 210 (-) AD

Gross Content: 1177 liters

Net Content: 875 liters

Display Area: 1,75 m²

Ambient Temperature: +16 bis +25 °C

Temperature Range: -18 °C bis -23 °C

Rated Voltage / Normal Frequency: 220 - 240 V / 50 Hz

:Version of Chiller

Manufacturer: AHT

Model: Athen 210(-) AD

High energy savings compared to conventional compound systems

AHT e-economize: Additional high energy saving potential through comprehensive optimization in technology and design

Improved product inspection with optimized usable net content of chiller

Ecologically harmless by the natural refrigerant propane

Rated Power Consumption: 450 W
(Rated Power Consumption Light: ca. 28 W (optional)
Rated Current: 2.0 A
Protection: 16 A
Energy Consumption (at 25 °C): 8.7 kWh / 24 h
Length of Connection Cable: 1750 mm
Refrigerant: R290
Refrigerant Quantity: 110 g
Max. Permissible Operating Pressure: 30 bar
Length (Outside / Inside): 2102 / 1970 mm
Depth (Outside / Inside): 993 / 860 mm
Working Height (Front / Outside Height): 800 / 910 mm
Stacking Height: 600 mm
Weight (Net): 141 kg
(Lighting: LED (optional)
Year of construction: 2010 +/- 3 years

Completely CFC and HFC-free
Secured product quality due to constant
internal temperature with high power
reserves
Ready to plug in without installation effort
Low investment and operating costs
Refrigeration is maintenance free
Large curved glass sliding lid

SLV15CNX

معلومات عامة

- الموديل: SLV15CNX LBP R290 inverter blcd
- القدرة الحصانية: عادةً ما يكون تصنيف القدرة الحصانية لهذا الموديل هو **HP 5/8** (حوالي 0.625 HP).
- النوع: يُصنف كضاغط ضغط منخفض (LBP) مما يجعله مناسباً لتطبيقات التبريد.
- التوافق: متوافق مع موديل دانفوس 104H-8568 مما يدل على استخدامه في أنظمة التبريد المختلفة.

الاستخدامات

هذا الضاغط مصمم للكفاءة والموثوقية في إعدادات التبريد التجارية، وخاصةً حيث يتم استخدام غاز التبريد R290. يعد خياراً جيداً للمشاريع التي تتطلب أداءً عاليًا في بيئات العمل المختلفة.



Picture Private Copyright WWW.MBSMGROUP.TN

ATHEN 40XL(-)ADVS



AP

Serialnr: 280262 00001780

Gerätedaten
cabinet data

class 3 (25°C/60%RH)

(-)

Nennspannung/frequ. Nom Voltg./frequ.
Tension/Frequence nominale

220-240V/50Hz

Nennaufnahme Nom Consump
Prise de courant nominale

450 W

Nennstrom Nom Current
Courant nominal

2,0 A

Schutzart Protection class
Type de protection

-

Typ Type
Type

B 845N

Energieaufnahme Energy consump
Absorption d'energie

8,7 kWh/24h

Absicherung Fuse

16 A

Kältemittel(Menge) Refrigerant(Quan)
Type / Quantité de réfrigérant

R290/0,110 kg

Nettoinhalt Net Content
Capacité nette

811 dm³

max. zul. Betriebsüberdruck 30 bar
Eigensicher nach VV-VBG 20. § 7.3
Dichtheit geprüft

Surpression max. de service
Sécurité propre selon VV-
Imperméabilité examinée

Subile 30 bar
57.3



RoHS

ENTSORGEN SIE DIESE WÄRMEDÄMMUNG MIT PENS...
Das Gas ist nicht...
Die Rohrlängen nicht bes...
DIE WÄRMEDÄMMUNG...
THE CANNOT BE RE...
with local waste...
be sure that th...
REUSE AU REB...
OLATION THE...
la mise au rébu...
avec l'indorm...





Picture Private Copyright WWW.MBSMGROUP.TN