


NT6222GK

تقنية: Category

2024، نوفمبر، written by Mahdi MILED | 18



A - APPLICATION / LIMIT WORKING CONDITIONS			
1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	200-240 V 50 Hz / 230 V 60 Hz		
4 Application type	Medium Back (for commercial compressors)		
4.1 Evaporating temperature range	-20 to 0 °C (-4°F to 32°F)		
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube expansion valve		
8 Compressor cooling	Operating voltage		
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm ²] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm ²] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	
B - MECHANICAL DATA			
1 Commercial designation	1	[hp]	
2 Displacement	17.39	[cm ³] (1.061 cu.in)	
2.1 Bore [mm]	34.120		
2.2 Stroke [mm]	19.030		
3 Lubricant charge	450	[ml] (15.22 fl.oz.)	
3.1 Lubricants approved			
3.2 Lubricants type/viscosity	ESTER / ISO22		
4 Weight (with oil charge)	17	[kg] (37.48 lb.)	
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)	
C - ELECTRICAL DATA			
1 Nominal Voltage/Frequency/Number of Phases	200-240 V 50 Hz / 230 V 60 Hz 1 ~ (Single phase)		
2 Starting device type	Current Relay		
2.1 Starting device	MTRPH-60-59		
3 Start capacitor	130-156(330)	[µF(VAC minimum)]	
4 Run capacitor	-	[µF(VAC minimum)]	
5 Motor protection	T0750/G6		
6 Start winding resistance	10.10	[Ω at 25°C (77°F)] +/- 8%	
7 Run winding resistance	1.75	[Ω at 25°C (77°F)] +/- 8%	
8 LRA - Locked rotor amperage (50 Hz)	37.00	[A] - Measured according to UL 984	



Aspera, Embraco, NT6222GK, R404A, R449A, R407A, R452A, MHbp, 1 Hp, Dis 17.39 cm³

Embraco NT6222GK ضاغط

Embraco NT6222GK هو ضاغط هيرميتي مصمم لتطبيقات التبريد، ويعتبر مناسباً للضغط المتوسط والعالي. إليك بعض المعلومات الأساسية حوله:

المواصفات

- الموديل: NT6222GK
- النوع: ضاغط مكبس هيرميتي
- الغازات المبردة: متوافق مع R404A و R507 و R452A
- القوة: 1 حصان (حوالي 0.75 كيلو واط)
- الجهد الكهربائي: يعمل على 220-240 فولت، 50 هرتز
- حجم الأسطوانة: 17.39 سم³
- نوع التيار: أحادي الطور (مونوفاز)
- الوزن: حوالي 17.2 كجم

التطبيقات

يستخدم NT6222GK بشكل أساسي في:

- أنظمة التبريد ذات الضغط المتوسط والعالي.
- وحدات التبريد التجارية حيث تكون الكفاءة والموثوقية ضرورية.

الأداء

تم تصميم هذا الضاغط ليعمل بكفاءة في درجات الحرارة المنخفضة، مما يجعله مناسباً لمهام التبريد المختلفة، بما في ذلك:

- برادات المشروبات
- حاويات العرض
- المجمدات

مميزات إضافية

- يأتي الضاغط مزوداً بالمكونات الكهربائية اللازمة للتشغيل.
- تم تصميمه ليتوافق مع المعايير القياسية وفقاً للوائح EN12900.

يعتبر NT6222GK خياراً قوياً لمن يحتاجون إلى حلول تبريد موثوقة في البيئات التجارية.



embraco **NT6222GK**

THERMALLY PROTECTED		220-240 V~50 Hz
	R 404A	
POE. OIL 450CC	1 PH	

MADE IN SLOVAKIA · NO START WITHOUT STARTING DEVICE

922CA04 GE M17MFPBT

Picture Private Copyright WWW.MBSMGROUP.TN

[تنزيل NT6222GK](#)