

GL99BL

تقنية :Category

2024, نوفمبر written by Mahdi MILED | 22

Model / Modèle / Modello	Power / Potencia / Leistung / Potenza	Cop cooling / Coef. de Kälteleistung / Refrigeration	Displacement / Hubraum / Cylinder	Evaporating temp. / Temp. d'évaporation / Verdampfungstemp. / Temp. d'evaporazione	Expansion / Expansión / Entspannung / Dilatación	Oil / Aceite / Öl / Hale	Weight / Peso / Gewicht / Poids	Motor / Motor / Motor / Motor							
LBP R134a 50 Hz				CECOMAF (W) -35 -30 -25 -10		ASHRAE -23.3 kcal/h COP		R134a 50 Hz							
GD24AA	1/20 S	2.42	12	21	34	0.51	84	41	0.68	C	100	5.3	RSR	P	
GD30AA	1/12 S	3.08	22	36	52	0.74	116	62	0.96	C	150	5.8	RSR	P	
GD36AA	1/12 S	3.62	28	43	61	0.76	135	72	0.99	C	200	5.9	RSR	P	
GD40AA	1/10 S	4.03	34	49	70	0.77	154	82	1.00	C	200	6.7	RSR	P	
GL45AA	1/8 S	4.55	37	56	81	0.81	183	96	1.06	C	265	8.3	RSR	P	
GL45AAb	1/8 S	4.55	37	56	81	0.81	183	96	1.06	C	265	8.3	CSR	R	
GL50AA	1/7 S	5.12	41	63	91	0.83	204	107	1.08	C	265	8.9	RSR	P	
GL60AA	1/6 S	5.99	50	75	107	0.85	238	126	1.10	C	265	9.1	RSR	P	
GL60AAb	1/6 S	5.99	50	75	107	0.85	238	126	1.10	C-V	265	9.1	CSR	R	
GL60BH	1/6 OC	5.99	60	83	114	1.01	248	133	1.31	C	400	10.2	RSCR	P	
GL70AA	1/5 S	6.65	57	85	121	0.87	267	142	1.12	C	345	9.6	RSR	P	
GL75AA	1/5 S	7.39	68	95	132	0.91	296	155	1.18	C	345	9.9	RSR	P	
GL80AA	1/5 S	8.10	68	101	144	0.89	326	170	1.15	C	345	9.9	RSR	P	
GL80AAb	1/5 S	8.10	68	101	144	0.89	326	170	1.15	C-V	345	9.9	CSR	R	
GL80BH	1/5 OC	8.10	76	107	149	1.04	333	175	1.35	C	470	10.8	RSCR	P	
GL80DA	1/5 S	8.10	68	101	144	0.89	326	170	1.15	C-V	345	9.9	CSR	R	
GL90AA	1/4 S	9.08	82	119	165	0.90	350	193	1.15	C	345	10.2	RSR	P	
GL90AAb	1/4 S	9.08	82	119	165	0.90	350	193	1.15	C-V	345	10.2	CSR	R	
GL90BH	1/4 OC	9.08	82	119	165	0.96	350	193	1.25	C	470	11.1	RSCR	P	
GL90DA	1/4 S	9.08	82	119	165	0.90	350	193	1.15	C-V	400	10.3	CSR	R	
GL99AA	1/4 S	9.93	83	124	175	0.92	377	205	1.19	C	445	11.0	RSR	P	
GL99AAb	1/4 S	9.93	83	124	175	0.92	377	205	1.19	C-V	445	11.0	CSR	R	
GL99BH	1/4 OC	9.93	89	130	180	1.00	381	210	1.29	C	470	11.3	RSCR	P	
GP12AB	1/3 S	12.00	83	131	190	0.88	424	225	1.14	C	400	11.5	RSR	R	
GP12BB	1/3 OC	12.00	83	131	190	0.88	424	225	1.14	C	400	11.5	RSR	R	
GP12CB	1/3 F	12.00	83	131	190	0.88	424	225	1.14	C	400	11.5	RSR	R	
GP12FB	1/3 F	12.00	83	131	190	0.88	424	225	1.14	C-V	400	11.5	CSR	R	
GP14BB	3/8 OC	14.00	99	158	228	0.90	509	270	1.16	C	400	11.5	RSR	R	
GP14CB	3/8 F	14.00	99	158	228	0.90	509	270	1.16	C	400	11.5	RSR	R	
GP14EB	3/8 OC	14.00	99	158	228	0.90	509	270	1.16	C-V	400	11.5	CSR	R	
GP14FB	3/8 F	14.00	99	158	228	0.90	509	270	1.16	C-V	400	11.5	CSR	R	
GP16BB	3/8 OC	16.14	108	182	266	0.89	584	315	1.14	C	530	12.0	RSR	R	
GP16CB	3/8 F	16.14	108	182	266	0.89	584	315	1.14	C	530	12.0	RSR	R	
GP16FB	3/8 F	16.14	108	182	266	0.89	584	315	1.14	C-V	530	12.0	CSR	R	
GX18FB	3/7 F	18.40	123	199	291	0.91	660	345	1.18	C-V	500	15.1	CSR	R	
GX21FB	2/3 F	20.72	151	243	351	0.93	778	415	1.20	C-V	500	15.7	CSR	R	
200-240/220-230V 50/60Hz -I															
GL24AA	1/20 S	2.42	12	21	34	0.51	84	41	0.68	C	100	5.3	RSR	P	

Picture Private Copyright WWW.MBSMGROUP.TN

Huaguang, Compressor, GL99BL, lbp, 1/4h ,